

Project Num.

Date



General features

Description: LED fitting for lighting paths and urban spaces

Insulation class: class II (class I on request)

Nominal voltage: 220-240 V 50/60 Hz

Protection level IP: IP66

Protection against impact: IK09

Surge Protection Device: integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM

Power factor: > 0.90

Ambient temperature Ta: -30°C +50°C

Weight: 12.00 kg

Maximum exposed surface: 0,34 m²



Lateral exposed surface: 0.05 m²

Common mode overvoltage protection: 10 kV

Differential mode overvoltage protection: 10 kV

Driver: included

Labels and Certifications: ENEC / CE



Performance Data*

LED current:	350 mA
Flux source:	6685 lm
Power source:	35 W
Efficiency of source:	191 lm/W
Flux fitting:	5480 lm
Power fitting:	39,5 W
Efficiency of fitting:	139 lm/W
Dazzling index category:	D6


Optical System
Source: LED R3
Colour temperature: 4000 K
Colour rendering index (CRI): ≥ 70 (Ra ≥ 80 on request)
Type of optics: street symmetrical SO-01
Optical unit lifetime: $>160,000\text{h}$ @700mA @Ta25°C TM21 L80B20 $>160,000\text{h}$ @700mA @Ta25°C TM21 L80B10
Photobiological safety class: EXEMPT GROUP
ULOR: 0%
DLOR: 100%
Luminous intensity category: G*4
Normative framework
EN605981 / EN60598-2-3 / EN62471 / EN61547

Installation and maintenance
Installation: on string suspension
\varnothing power cable: 10 ÷ 14 mm
Cable gland: PG16
Wiring plate substitutability: removable plate
Optical unit substitutability: LED disc replacement
Power supply compartment: independent from the optical system

Flux regulation	Standard	On request
Self-learning virtual midnight	X	
Constant Light Output (CLO)		X
1-10V Regulation		X
Main voltage variation	X	
Pilot line		X
DALI Regulation	X	
Remote control system (PLC) telemanagement		X
Wireless telemanagement		X
Motion / brightness detectors		X


Materials
Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)
Screen: tempered flat glass
Lenses: PMMA high transparent
Fastening system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)
Seal: expanded anti-age silicone foam
Screws: stainless steel AISI 304
Wiring plate: zinc-plated steel
Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance
Colors
Sablé 100 Noir
Cod. 01OR4D63039CHM4

Complements



01OR915C0

B82 Suspension kit for string \varnothing 6-12 mm.
Colour: Sablé 100 Noir.



06KS909C0

B89 Connector 4 wai IP68

NOTE

*Performance Data

Values indicated in this technical sheet are to be considered nominal values with a tolerance of +/-7%.

Data of the lighting source flux and efficiency refer to the LED module, without lenses. In case you need data of the LED module complete with lenses, please multiply the mentioned data by 0.9 factor.

General Data

The features of the product listed above may be subjected to change without notice. They will have to be confirmed in case of order. In order to facilitate a constant updating of their products, Cariboni Group reserves the right to make changes without prior notice.