

Product Sheet

Path Pole

Options: POLE H. 1000
Colour temperature: 4000 K
Type of optics: rotosymmetrical wide beam

06PT3A8405C

Colour: Sablé 100 Noir




Project Num.

Date



General features

Description: Bollard
Insulation class: class II
Nominal voltage: 230 V 50 Hz
Protection level IP: IP65
Protection against impact: IK07
Power factor: > 0.90
Ambient temperature Ta: -30°C +50°C
Weight: 9.00 kg
Driver: included
Labels and Certifications: CE
Warranty: 5 years for LED fittings



Performance Data*

| | |
|----------------|---------|
| LED current: | 500 mA |
| Flux source: | 1390 lm |
| Power source: | 12 W |
| Flux fitting: | 1000 lm |
| Power fitting: | 14 W |

Optical System

Source: 8 LEDs

Colour temperature: 4000 K

Type of optics: rotosymmetrical wide beam

Normative framework

EN605981 / EN60598-2-1 / EN62471

Installation and maintenance

Installation: ground

Fastening: Screw anchors (or anchoring bolts available as an accessory)

Ø power cable: 8 ÷ 12 mm

Cable gland: M20

Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Diffusor: highly transparent polycarbonate

Floodlight: torned aluminium sheet for fastening metal anchors

Seal: extruded anti-age silicone

Screws: stainless steel AISI 304

Finish: phospho-chromatation


Colors

Sablé 100 Noir

Cod. **06PT3A8405C**

grey RAL9006

Cod. **06PT3A8405A**

Complements

06PY999X0

Anchoring bolts kit



06PT997C0

2 petals kit Colour: dark grey sablé 100 noir.

NOTE***Performance Data**

Values indicated in this technical sheet are to be considered nominal values with a tolerance of +/-7%.

Data of the lighting source flux and efficiency refer to the LED module, without lenses. In case you need data of the LED module complete with lenses, please multiply the mentioned data by 0.9 factor.

General Data

The features of the product listed above may be subjected to change without notice. They will have to be confirmed in case of order.

In order to facilitate a constant updating of their products, Cariboni Group reserves the right to make changes without prior notice.