Options: FIN vertical Color Temperature: 4000 K Type of optics: AS-D Asymmetric diffused beam

06FI1A9409C Colour: Sablé 100 Noir



General Features

Description:

Insulation class: class I

Rated voltage: 230 V 50 Hz

Protection Grade: IP65

Impact protection: IK08

Power Factor: > 0.90

Ambient temperature Ta: -30°C +50°C


Weight: 4.70 kg


Max exposed surface: 0,06 m²

Lateral exposed surface: 0,05 m²

Driver: included

Marks and Certifications: CE





H (m)	Ø (m) Er	n(lux)
5	3,29x1,84	6
4	2,64x1,47	9
3	1,98x1,11	15
2	1,32x0,73	34
1	0,66x0,37	141

Performance Data*

LED Current:	500 mA
Source flux:	1805 lm
Source power:	14 W
Source efficiency:	129 lm/W
Device flux:	1300 lm
Device power:	16 W
Appliance efficiency:	81 lm/W

Product Sheet

Rev. 23/07/2024

Fin Wall-Recessed

Options: FIN vertical Color Temperature: 4000 K

Type of optics: AS-D Asymmetric diffused beam

06FI1A9409C

Colour: Sablé 100 Noir

Optical System

Source: 9 LEDs

Color Temperature: 4000 K

Color Rendering Index (CRI): ≥ 80

Chromatic consistency (SDCM): ≤ 3

Type of optics: AS-D Asymmetric diffused beam

Optical group life: >60.000h @Ta25°C L80B10

Normative References

EN60598-1 / EN60598-2-2 / EN62471

Installation and maintenance

Installation: wall installation

Fixing: Wall-recessed housing: stainless steel to be ordered separately (cod. 06FI990J0)

Ø power cable: 8 ÷ 12 mm

Cable gland: M20

Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Diffuser: sandblasted flat glass

Seals: EPDM die cut / printed

Screws: stainless steel AISI 304

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

Colors

Sablé 100 Noir Code: **06FI1A9409C**



Product Sheet

Rev. 23/07/2024

Fin Wall-Recessed


Options: FIN vertical Color Temperature: 4000 K

Type of optics: AS-D Asymmetric diffused beam

06FI1A9409C

Colour: Sablé 100 Noir

Complements



06FI990J0

Recessed housing

in AISI 430 steel for wall installation.

NOTES

*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering. In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.

