



**General Features**

|   |
|---|
| Description: LED fitting for lighting façades, paths and urban spaces |
| Insulation class: Class III   |
| Rated voltage: 24 Vdc   |
| Protection Grade: IP66  |
| Impact protection: IK07   |
| Surge protection device: integrated 2kV-4kV                           |
| Power Factor: > 0.95  |
| Ambient temperature Ta: -30°C +50°C                                   |
| Weight: 4.5 kg  |
| Max exposed surface: 0.04 m <sup>2</sup>                              |
| Lateral exposed surface: 0.021 m <sup>2</sup>                         |
| Common mode surge protection: 2 kV                                    |
| Overvoltage protection differential mode: 4 kV                        |
| Driver: remote (to be ordered separately)                             |
| Marks and Certifications: CE  |



**Performance Data\***

|                       |         |
|-----------------------|---------|
| Source flux:          | 1910 lm |
| Source power:         | 20 W    |
| Source efficiency:    | 96 lm/W |
| Device flux:          | 1330 lm |
| Device power:         | 22 W    |
| Appliance efficiency: | 60 lm/W |

**Optical System**

|  |
|--|
| Source: 5 LED                                  |
| Color Temperature: TW 2000K - 4000 K           |
| Color Rendering Index (CRI): $\geq 80$         |
| Chromatic consistency (SDCM): $\leq 3$         |
| Type of optics: D70°                           |
| Optical group life: >60.000 h @ Ta 25°C L80B10 |
| Photobiological safety class: EXEMPT GROUP     |
| ULOR: 0%                                       |
| DLOR: 100%                                     |
| BUG rating: B1-U0-G0                           |

**Normative References**

|   |
|---|
| EN60598-1 / EN60598-2-3 / EN61547 / EN62471 / EN55015 / EN61000-3-2 / EN61000-3-3 |
|---|

**Installation and maintenance**

|  |
|--|
| Installation: ground   |
| Tilt: -90° +130° continuously adjustable                     |
| Ø power cable: 7 ÷ 13 mm                                     |
| Cable Gland: M20   |
| Power supply compartment: independent from the optical group |

**Flow adjustment**

|              | Standard |
|--------------|----------|
| DALI control | X        |

**Materials**

|  |
|--|
| Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)   |
| Screen: tempered flat glass 4 mm   |
| Lenses: high-transparency PMMA   |
| Seals: anti-age silicone   |
| Screws: stainless steel AISI 304   |
| Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance |

**Colors**

|                  |                                |
|------------------|--------------------------------|
| ■ Sablé 100 Noir | Code: <b>06KI3C0506C15CHS6</b> |
|------------------|--------------------------------|

Complements



06KI905X0  
D9 Connection kit



06KI908X0  
D12 Driver Kit

Complements



06KI912X0  
Kit cable



06KI913X0  
Kit cable



06KI914X0  
Kit cable



06KI911X0  
Wall Spacer

---

**Product Sheet**

30/07/2024

**Kinetic Ceiling**

Size: Monoemission

Color Temperature: TW 2000K - 4000 K

Type of optics: D70°

**06KI3C0506C15CHS6**Colour: Sablé 100 Noir

---

---

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.