



**General Features**

Description: LED fitting for lighting façades, paths and urban spaces

Insulation class: Class II

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66

Impact protection: IK07

Surge protection device: integrated 2kV-4kV

Power Factor: > 0.95

Ambient temperature Ta: -30°C +50°C

Weight: 6.2 kg

Max exposed surface: 0.04 m<sup>2</sup>



Lateral exposed surface: 0.021 m<sup>2</sup>

Common mode surge protection: 2 kV

Overvoltage protection differential mode: 4 kV

Driver: included

Marks and Certifications: CE



Performance Data*	ELL50x18_UP	D70_DOWN
Source flux:	2210 lm	2210 lm
Source power:	16 W	16 W
Source efficiency:	138 lm/W	138 lm/W
Device flux:	1610 lm	1480 lm
Device power:	18 W	18 W
Appliance efficiency:	92 lm/W	85 lm/W

**Optical System**

Source: 10 LED
Color Temperature: 4000 K
Color Rendering Index (CRI): ≥ 80
Chromatic consistency (SDCM): ≤ 3
Type of optics: ELL50°x18° + D70°
Optical group life: >60.000 h @ Ta 25°C L80B10
Photobiological safety class: EXEMPT GROUP
ULOR: 0%
DLOR: 100%

**Normative References**

EN60598-1 / EN60598-2-3 / EN61547 / EN62471 / EN55015 / EN61000-3-2 / EN61000-3-3
---

**Installation and maintenance**

Installation: ceiling
Tilt: -90° +130° continuously adjustable
Ø power cable: 7 ÷ 13 mm
Cable Gland: M20
Power supply compartment: independent from the optical group

**Flow adjustment**

	Standard
DALI control	X

**Materials**

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)
Screen: tempered flat glass 4 mm
Lenses: high-transparency PMMA
Seals: anti-age silicone
Screws: stainless steel AISI 304
Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

**Colors**

 White RAL9003	Code: <b>06KI4E01200C33DHL</b>
---	--------------------------------

**Product Sheet**

30/07/2024

**Kinetic Wall**

Size: Biemission

Color Temperature: 4000 K

Type of optics: ELL50°x18° + D70°

**06KI4E01200C33DHL**

Colour: White RAL9003

**Complements**

06KI911X0

Wall Spacer

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.