





General Features

- Description: LED fitting for lighting façades, paths and urban spaces
- Insulation class: Class III
- Rated voltage: 24 Vdc
- Protection Grade: IP66
- Impact protection: IK07
- Surge protection device: integrated 2kV-4kV
- Power Factor: > 0.95
- Ambient temperature Ta: -30°C +50°C
- Weight: 6.2 kg
- Max exposed surface: 0.04 m²
- Lateral exposed surface: 0.021 m²
- Common mode surge protection: 2 kV
- Overvoltage protection differential mode: 4 kV
- Driver: remote (to be ordered separately)
- Marks and Certifications: CE



| Performance Data* | G30x18_UP | ELL50x18_DOWN |
|-----------------------|-----------|---------------|
| Source flux: | 1910 lm | 1910 lm |
| Source power: | 20 W | 20 W |
| Source efficiency: | 96 lm/W | 96 lm/W |
| Device flux: | 1360 lm | 1445 lm |
| Device power: | 21 W | 21 W |
| Appliance efficiency: | 65 lm/W | 69 lm/W |

Optical System

| |
|--|
| Source: 10 LED |
| Color Temperature: TW 2000K - 4000 K |
| Color Rendering Index (CRI): ≥ 80 |
| Chromatic consistency (SDCM): ≤ 3 |
| Type of optics: G30°x18° + ELL50°x18° |
| Optical group life: >60.000 h @ Ta 25°C L80B10 |
| Photobiological safety class: EXEMPT GROUP |
| ULOR: 0% |
| DLOR: 100% |

Normative References

| |
|---|
| EN60598-1 / EN60598-2-3 / EN61547 / EN62471 / EN55015 / EN61000-3-2 / EN61000-3-3 |
|---|

Installation and maintenance

| |
|--|
| Installation: ceiling |
| Tilt: -90° +130° continuously adjustable |
| Ø power cable: 7 ÷ 13 mm |
| Cable Gland: M20 |
| Power supply compartment: independent from the optical group |

Flow adjustment

| | Standard |
|--------------|----------|
| DALI control | X |


Materials

| |
|--|
| Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%) |
| Screen: tempered flat glass 4 mm |
| Lenses: high-transparency PMMA |
| Seals: anti-age silicone |
| Screws: stainless steel AISI 304 |
| Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance |

Colors


| | |
|---|--------------------------------|
|  White RAL9003 | Code: 06KI4E0506C24DHS6 |
|---|--------------------------------|

Complements



06KI906X0


D10 Connection Kit



06KI909X0


D13 Kit driver

Complements




06KI912X0

Kit cable




06KI913X0

Kit cable



06KI914X0

Kit cable



06KI911X0

Wall Spacer

Product Sheet

30/07/2024

Kinetic Wall

Size: Biemission

Color Temperature: TW 2000K - 4000 K

Type of optics: G30°x18° + ELL50°x18°

06KI4E0506C24DHS6Colour: White RAL9003

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.