




**General Features**

Description:	LED luminaire
Insulation class:	class II
Rated voltage:	230 V 50 Hz
Protection Grade:	IP66
Impact protection:	IK07
Power Factor:	> 0.90
Ambient temperature Ta:	-30°C +50°C
Weight:	3.00 kg
Max exposed surface:	0,08 m <sup>2</sup>
Lateral exposed surface:	0,0165 m <sup>2</sup>
Common mode surge protection:	6 kV
Overvoltage protection differential mode:	10 kV
Drivers:	included
Marks and Certifications:	ENEC / CE



**Performance Data\***

LED Current:	700 mA	525 mA	350 mA
Source flow:	6075 lm	4790 lm	3370 lm
Source power:	36 W	26.5 W	17.5 W
Source efficiency:	169 lm/W	181 lm/W	193 lm/W
Device flow:	5150 lm	4055 lm	2855 lm
Device power:	40.5 W	31 W	21 W
Appliance efficiency:	127 lm/W	131 lm/W	136 lm/W
Glare Index Category:	D0	D0	D2

### Optical System

Source: LED R1,5
Color Temperature: 4000 K
Color Rendering Index (CRI): $\geq 70$
Color Consistency (SDCM): $\leq 4$
Type of optics: street
Optical group life: >160.000h @700mA @Ta25°C TM21 L80B20 >160.000h @700mA @Ta25°C TM21 L80B10
Photobiological safety class: EXEMPT GROUP
ULOR: 0%
DLOR: 100%
Light intensity category: G*2

### Normative References

EN60598-1 / EN60598-2-3 / EN60598-2-5 / EN62471 /  
EN61547

### Installation and maintenance

Installation: wall / ground / pole
Pole diameter: Ø 60 - 76 - 102 mm
Fixing: post top + Ø 48/60 mm bracket, fixed or adjustable with a 15° step / wall-mounted, fixed or adjustable with a 15°
Ø power cable: 10 ÷ 14 mm
Cable gland: PG11

### Flow adjustment

Standard On request

Virtual Midnight Teaching	X
Arrangement for Zhaga connector (Book 18)	X
Adjusting 1-10V	X
DALI control	X
Mains voltage variation	X
Pilot line	X
Power line telemanagement (PLC)	X
Wireless remote management	X
Provision for motion/light sensors	X

### Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)
Lenses: PMMA
Seals: extruded anti-age silicone
Screws: stainless steel AISI 304
Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

### Colors

 Grey RAL9006	Code: <b>06LV3B8008AHM3</b>
--	-----------------------------

## Complements



06AK903A0

L3 Single joint kit  
for Ø 60-76 mm poles. Colour: grey  
RAL9006.



06AK904A0

L4 Double joint kit  
for Ø 60-76 mm poles. Colour: grey  
RAL9006.



06AK910A0

L12 joint for Ø 60-48 mm pole.  
Colour: grey RAL9006.



06AK952A0

L9 Joint LEVANTE SMALL  
for Ø 60 mm pole. Colour: grey  
RAL9006.



06AK905A0

B153 Post top joint  
Ø 60mm (h.90mm). Colour: grey  
RAL9006.




01AK921A0

B1 Double tubular arm  
Ø 60 mm for poles Ø 60-76 mm. L=550  
mm. Colour: grey RAL9006.




01AK922A0

B2 Double tubular arm  
Ø 60 mm for poles Ø 60-76 mm. L=550  
mm. Colour: grey RAL9006.



06AK921A0

B1 Single arm  
Ø 60 mm for poles Ø 60-76 mm. L=550  
mm. Colour: grey RAL9006.



06AK922A0

B2 Double arm  
Ø 60 mm for poles Ø 60-76 mm. L=550  
mm. Colour: grey RAL9006.

---

**Product Sheet**

Rev. 25/03/2022

**Levante Pole Side**


Size: small

Color Temperature: 4000 K

Type of optics: street

**06LV3B8008AHM3**Colour: Grey RAL9006

---



06AK951A0

B1-P Wall-mounted arm.

Colour: grey RAL9006.

---

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.