



General Features

Description: LED luminaire
Insulation class: class II
Rated voltage: 230 V 50 Hz
Protection Grade: IP66
Impact protection: IK07
Surge protection device: integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM
Power Factor: > 0.90
Ambient temperature Ta: -30°C +50°C
Weight: 8.00 kg
Max exposed surface: 0,17 m²
Lateral exposed surface: 0,04 m²
Common mode surge protection: 10 kV
Overtoltage protection differential mode: 10 kV
Drivers: included
Marks and Certifications: ENEC / CE



Performance Data*

LED Current:	700 mA	525 mA	350 mA
Source flow:	8460 lm	6670 lm	4695 lm
Source power:	48 W	35.5 W	23 W
Source efficiency:	176 lm/W	188 lm/W	204 lm/W
Device flow:	7275 lm	5740 lm	4040 lm
Device power:	52.5 W	39.5 W	26.5 W
Appliance efficiency:	139 lm/W	145 lm/W	152 lm/W
Glare Index Category:	D6	D6	D6

Optical System

Source: LED R2
Color Temperature: 4000 K
Color Rendering Index (CRI): ≥ 70
Color Consistency (SDCM): ≤ 4
Type of optics: pedestrian crossing AP-01_SX
Optical group life: >160.000h @700mA @Ta25°C TM21 L80B20 >160.000h @700mA @Ta25°C TM21 L80B10
Photobiological safety class: EXEMPT GROUP
ULOR: 0%
DLOR: 100%
Light intensity category: G*6

Normative References

EN60598-1 / EN60598-2-3 / EN60598-2-5 / EN62471 / EN61547

Installation and maintenance

Installation: wall / pole
Pole diameter: Ø 60 - 76 - 102 mm
Tilt: fastened or adjustable with step 15°
Fixing: post top + Ø 48/60 mm bracket, fixed or adjustable with a 15° step / wall-mounted, fixed or adjustable with a 15°
Ø power cable: 10 ÷ 14 mm
Cable gland: PG16

Flow adjustment

Standard On request

Virtual Midnight Teaching	X
Arrangement for Zhaga connector (Book 18)	X
Constant flow output (CLO)	X
Adjusting 1-10V	X
DALI control	X
Mains voltage variation	X
Pilot line	X
Power line telemanagement (PLC)	X

Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)
Screen: tempered flat glass
Lenses: PMMA
Seals: extruded anti-age silicone
Screws: stainless steel AISI 304
Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

Colors

 Grey RAL9006	Code: 06LV6C40034AHM3
--	------------------------------

Complements



06AK903A0

L3 Single joint kit
for Ø 60-76 mm poles. Colour: grey
RAL9006.



06AK904A0

L4 Double joint kit
for Ø 60-76 mm poles. Colour: grey
RAL9006.



06AK910A0

L12 joint for Ø 60-48 mm pole.
Colour: grey RAL9006.



06AK954A0

L10 Joint LEVANTE MEDIUM
for Ø 60 mm pole. Colour: grey
RAL9006.



06AK955A0

L11 Joint LEVANTE MEDIUM
for wall-mounting. Colour: grey
RAL9006.



06AK905A0

B153 Post top joint
Ø 60mm (h.90mm). Colour: grey
RAL9006.



01AK921A0

B1 Double tubular arm
Ø 60 mm for poles Ø 60-76 mm. L=550
mm. Colour: grey RAL9006.



01AK922A0

B2 Double tubular arm
Ø 60 mm for poles Ø 60-76 mm. L=550
mm. Colour: grey RAL9006.



06AK921A0

B1 Single arm
Ø 60 mm for poles Ø 60-76 mm. L=550
mm. Colour: grey RAL9006.

Product Sheet

Rev. 25/03/2022

Levante Pole Side

Size: medium

Color Temperature: 4000 K

Type of optics: pedestrian crossing AP-01_SX

06LV6C40034AHM3

Colour: Grey RAL9006

**06AK922A0**

B2 Double arm

Ø 60 mm for poles Ø 60-76 mm. L=550

mm. Colour: grey RAL9006.

**06AK951A0**

B1-P Wall-mounted arm.

Colour: grey RAL9006.

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.