




General Features

Description:	LED luminaire
Insulation class:	class II
Rated voltage:	230 V 50 Hz
Protection Grade:	IP66
Impact protection:	IK07
Surge protection device:	integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM
Power Factor:	> 0.90
Ambient temperature Ta:	-30°C +50°C
Weight:	8.00 kg
Max exposed surface:	0,17 m ²
Lateral exposed surface:	0,04 m ²
Common mode surge protection:	10 kV
Overvoltage protection differential mode:	10 kV
Drivers:	included
Marks and Certifications:	ENEC / CE



Performance Data*

LED Current:	700 mA	525 mA	350 mA
Source flow:	15515 lm	12285 lm	8690 lm
Source power:	95 W	70.5 W	46.5 W
Source efficiency:	163 lm/W	174 lm/W	187 lm/W
Device flow:	13345 lm	10570 lm	7475 lm
Device power:	103.5 W	77.5 W	51.5 W
Appliance efficiency:	129 lm/W	136 lm/W	145 lm/W
Glare Index Category:	D5	D6	D6

Optical System

Source: LED R4

Color Temperature: 3000 K

Color Rendering Index (CRI): ≥ 70

Color Consistency (SDCM): ≤ 4

Type of optics: pedestrian crossing AP-01_SX

Optical group life: >160.000h @700mA @Ta25°C TM21
L80B20 >160.000h @700mA @Ta25°C TM21 L80B10

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Light intensity category: G*6

Normative References

EN60598-1 / EN60598-2-3 / EN60598-2-5 / EN62471 /
EN61547

Installation and maintenance

Installation: wall / pole

Pole diameter: \varnothing 60 - 76 - 102 mm

Tilt: fastened or adjustable with step 15°

Fixing: post top + \varnothing 48/60 mm bracket, fixed or adjustable
with a 15° step / wall-mounted, fixed or adjustable with a
15°

\varnothing power cable: 10 ÷ 14 mm

Cable gland: PG16

Flow adjustment

Standard On request

Virtual Midnight Teaching X

Arrangement for Zhaga connector
(Book 18) X

Constant flow output (CLO) X

Adjusting 1-10V X

DALI control X

Mains voltage variation X

Pilot line X

Power line telemanagement (PLC) X

Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper
content < 1%)

Screen: tempered flat glass

Lenses: PMMA

Seals: extruded anti-age silicone

Screws: stainless steel AISI 304

Finish: phospho-chromatation treated and polyester
powder-coated in 16 phases to increase weather resistance

Colors

■ Grey RAL9006


Code: **06LV6E80934AHM3**

Complements



06AK903A0

L3 Single joint kit
for Ø 60-76 mm poles. Colour: grey
RAL9006.



06AK904A0

L4 Double joint kit
for Ø 60-76 mm poles. Colour: grey
RAL9006.




06AK910A0

L12 joint for Ø 60-48 mm pole.
Colour: grey RAL9006.



06AK954A0

L10 Joint LEVANTE MEDIUM
for Ø 60 mm pole. Colour: grey
RAL9006.



06AK955A0

L11 Joint LEVANTE MEDIUM
for wall-mounting. Colour: grey
RAL9006.




06AK905A0

B153 Post top joint
Ø 60mm (h.90mm). Colour: grey
RAL9006.



01AK921A0

B1 Double tubular arm
Ø 60 mm for poles Ø 60-76 mm. L=550
mm. Colour: grey RAL9006.



01AK922A0

B2 Double tubular arm
Ø 60 mm for poles Ø 60-76 mm. L=550
mm. Colour: grey RAL9006.



06AK921A0

B1 Single arm
Ø 60 mm for poles Ø 60-76 mm. L=550
mm. Colour: grey RAL9006.

Product Sheet

Rev. 25/03/2022

Levante Pole Side

Size: medium

Color Temperature: 3000 K

Type of optics: pedestrian crossing AP-01_SX


06LV6E80934AHM3

Colour: Grey RAL9006

**06AK922A0**

B2 Double arm

Ø 60 mm for poles Ø 60-76 mm. L=550 mm. Colour: grey RAL9006.

**06AK951A0**

B1-P Wall-mounted arm.

Colour: grey RAL9006.

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.