



General Features

|   |                         |
|---|-------------------------|
| Description:                              | LED floodlight          |
| Insulation class:                         | class II                |
| Rated voltage:                            | 220-240 V 50/60 Hz      |
| Protection Grade:                         | IP66                    |
| Impact protection:                        | IK09                    |
| Surge protection device:                  | integrated 10kV-10kA    |
| Power Factor:                             | > 0.95                  |
| Ambient temperature Ta:                   | -30°C +50°C             |
| Weight:                                   | 6.8 kg                  |
| Max exposed surface:                      | 0.119 m²                |
| Lateral exposed surface:                  | 0.026 m²                |
| Common mode surge protection:             | 10 kV                   |
| Overvoltage protection differential mode: | 10 kV                   |
| Drivers:                                  | included                |
| Lifetime driver:                          | F10 >100.000h @ Ta 25°C |
| Marks and Certifications:                 | CE / ENEC (pending)     |



Performance Data\*

|                       |          |
|-----------------------|----------|
| Source flow:          | 6805 lm  |
| Source power:         | 32 W     |
| Source efficiency:    | 213 lm/W |
| Device flow:          | 5855 lm  |
| Device power:         | 36 W     |
| Appliance efficiency: | 163 lm/W |
| Glare Index Category: | D1       |

### Optical System

Source: LED R2

Color Temperature: 4000 K

Color Rendering Index (CRI):  $\geq 70$

Color Consistency (SDCM):  $\leq 3$

Type of optics: LA-03 Wide street

Optical group life: >100.000 h @ Ta 25°C L90B10

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Light intensity category: G\*3

BUG rating: B5-U0-G5

### Normative References

EN60598-1, EN60598-2-3, EN61547; EN62471, EN55015,  
EN61000-3-2, EN61000-3-3

### Installation and maintenance

Installation: wall / ceiling / pole; predisposition IN-OUT

Tilt:  $-90^{\circ} \div +90^{\circ}$  continuously

Fixing: steel bracket

Ø power cable: 10 ÷ 14 mm

Cable Gland: PG16

Power supply compartment: independent from the optical group

### Flow adjustment

On request

Virtual Midnight Teaching

X

Arrangement for Zhaga connector (Book 18)

X

Constant flow output (CLO)

X

Adjusting 1-10V

X

DALI control

X

Mains voltage variation

X

Wireless remote management

X

Provision for motion/light sensors

X

### Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Screen: tempered flat glass 4 mm

Lenses: high-transparency PMMA

Fixing system: painted RAL9006 steel adjustable bracket

Seals: anti-age silicone

Screws: stainless steel AISI 304 and 316

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

### Colors

■ Grey RAL9006

Code: **06NN2C436017AHM4**

## Product Sheet

30/04/2024

## Newton 2.0

Size: small

Color Temperature: 4000 K

Type of optics: LA-03 Wide street

**06NN2C436017AHM4**

Colour: Grey RAL9006

## Complements



06NW902A0

L14 Post top kit  
for Ø 76 mm poles. Colour: grey  
RAL9006. Newton 2.0 small/medium.



06NN902B0

B243 Visor kit.  
Newton 2.0 small. Colour: black  
RAL9005.

## NOTES

### \*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

### General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.