



**General Features**

|   |                          |
|---|--------------------------|
| Description:                              | LED floodlight           |
| Insulation class:                         | class II                 |
| Rated voltage:                            | 220-240 V 50/60 Hz       |
| Protection Grade:                         | IP66                     |
| Impact protection:                        | IK08                     |
| Power Factor:                             | > 0.90                   |
| Ambient temperature Ta:                   | -30°C +50°C              |
| Weight:                                   | 4.1 kg                   |
| Max exposed surface:                      | 0.047 m²                 |
| Lateral exposed surface:                  | 0.038 m²                 |
| Common mode surge protection:             | 10 kV                    |
| Overvoltage protection differential mode: | 6 kV                     |
| Driver:                                   | included                 |
| Driver lifetime:                          | >100.000h @Ta25°C L80B10 |
| Marks and Certifications:                 | CE                       |



**Performance Data\***

|                       |          |
|-----------------------|----------|
| LED Current:          | 700 mA   |
| Source flux:          | 4395 lm  |
| Source power:         | 31.5 W   |
| Source efficiency:    | 140 lm/W |
| Device flux:          | 3780 lm  |
| Device power:         | 35 W     |
| Appliance efficiency: | 108 lm/W |

### Optical System

Source: LED L4

Color Temperature: 3000 K

Color Rendering Index (CRI):  $\geq 80$

Chromatic consistency (SDCM):  $\leq 3$

Type of optics: M 25° Medium beam

Optical group life: >100.000h @Ta25°C L80B10

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Light intensity category: G\*6

### Normative References

EN60598-1 / EN60598-2-3 / EN62471 / EN61547

### Installation and maintenance

Installation: wall / ceiling / ground / side pole

Pole diameter:  $\varnothing$  102 mm

Tilt: -45° +90°, continuously-adjustable pointing and locking system.

Wiring: pre-wired product with cable and connector

$\varnothing$  power cable: 12 mm

Cable Gland: M20

Power supply compartment: independent from the optical group

### Flow adjustment

Standard

DALI control

X

### Materials

Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Screen: tempered flat glass

Lenses: high-transparency PMMA

Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 304

Wiring plate: zinc-plated steel

Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance

### Colors

■ Grey RAL9006

Code: **06OM6B609B9AHL**

## Complements



06OM904A0

B136 Single pole ring  
for Ø 102 mm. Colour: grey RAL9006.



06OM905A0

B137 Double pole ring  
for Ø 102 mm. Colour: grey RAL9006.



06KS909C0

B89 Connector 4 way IP68

## NOTES

### \*Performance data

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

### General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.