



General Features

Description: LED fitting for lighting façades, paths and urban spaces

Insulation class: class II

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66

Impact protection: IK09

Power Factor: > 0.9

Ambient temperature Ta: -25° C + 50°C

Weight: 7.5 kg

Max exposed surface: 0.157 m²

Lateral exposed surface: 0.063 m²

Common mode surge protection: 10 kV

Overvoltage protection differential mode: 10 kV

Driver: included

Driver lifetime: > 100.000 h @Ta 25° C

Marks and Certifications: CE / ENEC

Performance Data*

| | |
|-----------------------|----------|
| LED Current: | 360 mA |
| Source flux: | 2650 lm |
| Source power: | 18 W |
| Source efficiency: | 147 lm/W |
| Device flux: | 2285 lm |
| Device power: | 21 W |
| Appliance efficiency: | 109 lm/W |
| Glare Index Category: | D6 |

Optical System

| |
|--|
| Source: LED L4 |
| Color Temperature: 3000 K |
| Color Rendering Index (CRI): ≥ 80 |
| Chromatic consistency (SDCM): ≤ 3 |
| Type of optics: D 40° Wide beam |
| Optical group life: > 100.000 h @ 700mA @Ta 25° C L90B10 |
| Photobiological safety class: EXEMPT GROUP |
| ULOR: 0% |
| DLOR: 100% |
| Light intensity category: G*6 |
| BUG rating: B1-U0-G1 |

Normative References

| |
|---|
| EN60598-1 / EN60598-2-3 / IEC / TR62778 / EN62471 / EN61547 |
|---|

Installation and maintenance

| |
|--|
| Installation: wall |
| Tilt: 0° ÷ 90° |
| Ø power cable: 6 ÷ 11 mm |
| Cable Gland: PG13,5 |
| Power supply compartment: independent from the optical group |


Flow adjustment

| | |
|--------------|---------------|
| DALI control | Standard X |
|--------------|---------------|

Materials

| |
|--|
| Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%) |
| Screen: tempered flat glass |
| Lenses: high-transparency PMMA |
| Fixing system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%) |
| Seals: anti-age silicone foam |
| Screws: stainless steel AISI 304 |
| Wiring plate: zinc-plated steel |
| Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance |

Colors

| | |
|---|-----------------------------------|
|  Champagne | Code: 06SP2BB6409C0G6HL |
|---|-----------------------------------|

Product Sheet

Rev 16/07/2024

Spoon Wall

Size: large

Color Temperature: 3000 K

Type of optics: D 40° Wide beam

06SP2BB6409C0G6HLColour: Champagne

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.