



General Features

Description: LED luminaire

Insulation class: class II (class I on request)

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66

Impact protection: IK09

Surge protection device: integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM

Power Factor: > 0.90

Ambient temperature Ta: -30°C +50°C

Weight: 14.3 kg

Max exposed surface: 0.26 m²

Lateral exposed surface: 0.10 m²

Common mode surge protection: 10 kV

Overtoltage protection differential mode: 10 kV

Driver: included

Driver lifetime: >100.000h @700mA @Ta25°C \ <0,2% 1.000h

Marks and Certifications: ENEC / CE



Performance Data*

LED Current:	525 mA
Source flow:	14950 lm
Source power:	88.5 W
Source efficiency:	169 lm/W
Fitting flux:	12855 lm
Fitting power:	95.5 W
Fitting efficiency:	135 lm/W
Glare Index Category:	D4

Product Sheet

18/10/2022

Themelio Arm Suspension

Size: medium

Colour Temperature: 3000 K

Type of optics: street asymmetrical LA-01

01TH2G05931DHM4

Colour: White RAL9003

Optical System

Source: LED R5

Colour Temperature: 3000 K

Color Rendering Index (CRI): ≥ 70 Chromatic consistency (SDCM): ≤ 4

Type of optics: street asymmetrical LA-01

Optical group life: >160.000h @700mA @Ta25°C TM21
L80F10

Photobiological safety class: EXEMPT GROUP

ULOR: 0%

DLOR: 100%

Light intensity category: G*3

Normative ReferencesEN60598-1 / EN60598-2-3 / EN61547 / EN62471, EN55015 /
EN61000-3-2 / EN61000-3-3**Installation and maintenance**

Installation: arm suspension

Wiring: pre-wired product with cable and connector

Ø power cable: 10 ÷ 14 mm

Cable Gland: PG16

Replaceable wiring plate: removable plate

Replaceable optical unit: each LED module is replaceable

Screen opening: opening by clip, fall block

Power supply compartment: independent from the
optical system**Flux regulation**

Standard On request

Virtual Midnight Teaching

X

Arrangement for Zhaga connector
(Book 18)

X

Constant flow output (CLO)

X

Adjusting 1-10V

X

DALI control

X

Mains voltage variation

X

Pilot line

X

Power line telemanagement (PLC)

X

Wireless remote management

X

Arrangement for motion /
brightness sensors

X

MaterialsBody: die-cast aluminium alloy UNI EN AB 47100 (copper
content < 1%)

Screen: tempered flat glass

Lenses: high-transparency PMMA

Fitting system: die-cast aluminium alloy UNI EN AB 47100
(copper content < 1%)

Seals: expanded anti-age silicone foam

Screws: stainless steel AISI 304

Wiring plate: zinc-plated steel

Finish: phospho-chromatation treated and polyester
powder-coated in 16 phases to increase weather resistance**Colours**

■ White RAL9003

Code: **01TH2G05931DHM4**

Complements



01TH900C0

C1 3/4" GAS suspension

Colour: Sablè 100 Noir.



01TH903C0

C4 Pulley suspension

Colour: Sablè 100 Noir.



01TH904C0

C5 Suspension for arm

Ø60 mm. Colour: Sablè 100 Noir.



01AK988C0

B212 Single arm

for poles Ø 60-76 mm. Colour: Sablé 100 Noir.



01AK989C0

B213 Double arm

for poles Ø 60-76 mm. Colour: Sablé 100 Noir.



01AK990C0

B214 Single arm

for poles Ø 102 mm. Colour: Sablé 100 Noir.



01AK991C0

B215 Double arm

for poles Ø 102 mm. Colour: Sablé 100 Noir.



01AK992C0

B216 Single arm

for poles Ø 60-76 mm. Colour: Sablé 100 Noir.



01AK994C0

B217 Double arm

for poles Ø 60-76 mm. Colour: Sablé 100 Noir.

Product Sheet

18/10/2022

Themelio Arm Suspension

Size: medium

Colour Temperature: 3000 K

Type of optics: street asymmetrical LA-01

01TH2G05931DHM4

Colour: White RAL9003

**01AK995C0**

B218 Single arm
for poles Ø 102 mm. Colour: Sablé 100
Noir.

**01AK996C0**

B219 Double arm
for poles Ø 102 mm. Colour: Sablé 100
Noir.

**01AK983C0**

B207-P Suspension wall-mounted
arm. Colour: Sablé 100 Noir.

**01AK935C0**

B15 Single curved arm
Ø 60 mm for poles Ø 102 mm. L=810
mm. Colour: Sablé 100 Noir.

**01AK936C0**

B16 Double curved arm
Ø 60 mm for poles Ø 102 mm. L=810
mm. Colour: Sablé 100 Noir.

**01AK950C0**

B15-P Curved wall-mounted arm
Ø 60 mm. L=840 mm. Colour: Sablé
100 Noir.

NOTES***Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

General Data

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.