



### General Features

Description: LED luminaire

Insulation class: class II (class I on request)

Rated voltage: 220-240 V 50/60 Hz

Protection Grade: IP66

Impact protection: IK09

Surge protection device: integrated 10kV-10kA, Type 3, equipped with LED signaling and thermofusible for disconnection at the end of life; impulse withstand CL II 10kV DM

Power Factor: > 0.90

Ambient temperature Ta: -30°C +50°C

Weight: 12 kg

Max exposed surface: 0.28 m<sup>2</sup>

Lateral exposed surface: 0.09 m<sup>2</sup>


Common mode surge protection: 10 kV

Overvoltage protection differential mode: 10 kV

Driver: included

Driver lifetime: >100.000h @700mA @Ta25°C \ <0,2% 1.000h

Marks and Certifications: ENEC / CE



### Performance Data\*

|                       |          |
|-----------------------|----------|
| LED Current:          | 350 mA   |
| Source flow:          | 3590 lm  |
| Source power:         | 23 W     |
| Source efficiency:    | 156 lm/W |
| Fitting flux:         | 3090 lm  |
| Fitting power:        | 26.5 W   |
| Fitting efficiency:   | 117 lm/W |
| Glare Index Category: | D5       |

### Optical System

|   |
|---|
| Source: LED R2  |
| Colour Temperature: 2200 K  |
| Color Rendering Index (CRI): $\geq 70$  |
| Chromatic consistency (SDCM): $\leq 4$  |
| Type of optics: street symmetrical SO-01  |
| Optical group life: >160.000h @700mA @Ta25°C TM21 L80B20 >160.000h @700mA @Ta25°C TM21 L80B10 |
| Photobiological safety class: EXEMPT GROUP  |
| ULOR: 0%  |
| DLOR: 100%  |
| Light intensity category: G*4   |

### Normative References

EN60598-1 / EN60598-2-3 / EN61547 / EN62471, EN55015 / EN61000-3-2 / EN61000-3-3

### Installation and maintenance

|  |
|--|
| Installation: suspension for string $\varnothing 6 \div 12$ mm, inclination horizontal $\pm 15^\circ$ , adjustability $0^\circ \div 360^\circ$ |
| $\varnothing$ power cable: $10 \div 14$ mm   |
| Cable Gland: PG16  |
| Replaceable wiring plate: removable plate  |
| Replaceable optical unit: each LED module is replaceable   |
| Screen opening: opening by clip, fall block  |
| Disconnecter: automatic (with terminal section 2.5 mm <sup>2</sup> )   |
| Power supply compartment: independent from the optical system  |

### Flux regulation

Standard On request

|   |   |
|---|---|
| Virtual Midnight Teaching                   | X |
| Arrangement for Zhaga connector (Book 18)   | X |
| Constant flow output (CLO)                  | X |
| Adjusting 1-10V                             | X |
| DALI control                                | X |
| Mains voltage variation                     | X |
| Pilot line                                  | X |
| Power line telemanagement (PLC)             | X |
| Wireless remote management                  | X |
| Arrangement for motion / brightness sensors | X |

### Materials

|  |
|--|
| Body: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)   |
| Screen: tempered flat glass  |
| Lenses: high-transparency PMMA   |
| Fitting system: die-cast aluminium alloy UNI EN AB 47100 (copper content < 1%)                               |
| Seals: expanded anti-age silicone foam   |
| Screws: stainless steel AISI 304   |
| Wiring plate: zinc-plated steel  |
| Finish: phospho-chromatation treated and polyester powder-coated in 16 phases to increase weather resistance |

### Colours

|  |                              |
|--|------------------------------|
|  Sablé 100 Noir | Code: <b>01VO6C43139CHM4</b> |
|--|------------------------------|

---

**Product Sheet**

Rev 12/10/2022

**Volta String Suspension**

Size: medium

Colour Temperature: 2200 K

Type of optics: street symmetrical SO-01

**01VO6C43139CHM4**Colour: Sablé 100 Noir

---

---

**NOTES****\*Performance data**

The values indicated in this data sheet are nominal values with a tolerance of +/-7%.

Source flux and source efficiency data refer to the LED module without optics; in case you are interested in the performance of the LED module complete with optical system, you must multiply the data reported by the factor 0.9.

**General Data**

The characteristics of the product listed may be subject to change and must be confirmed when ordering.

In order to promote constant updating of its products, Cariboni Group reserves the right to make changes without prior notice.